



- Wheel Position: Chip & Cut, All wheel
- For mixed road surface
- Good wear-resistance
- Strong carcass
- Excellent traction
- Resistant to puncture

RF/GF 118

Product Number	Tire Size	PR	Pattern	Weight (lbs/kg)	Rim Size (in)	Tread Depth (32nds/m m)	Load Index S/D & Speed S	Section Width (in/mm)	Overall Diameter (in/mm)	Max. Air Single-Dual (psi/kpa)	Load Capacity Single-Dual (lbs/kg's)	Qty/40"HC	Price
63920	8.25R20	16	RF/GF 118	98/44.4	6.5	18.5/15	137/137 & K	9.25/235	38.3/973	110/770-110/770	5355/2429-5070/2300	350 sets	
63901	9.00R20	16	RF/GF 118	121/54.8	7.0	19.5/15.5	144/142 & K	10.2/259	40.1/1019	130/900-130/900	6170/2799-5840/2650	310 sets	
63902	10.00R20	18	RF/GF 118	136/61.6	7.5	21.0/16.5	149/146 & K	10.9/278	41.5/1054	135/930-135/930	7160/3248-6610/2998	274 sets	
63903	11.00R20	18	RF/GF 118	156/70.7	8.0	21.5/17	152/149 & K	11.5/293	42.7/1085	135/930-135/930	7820/3547-7160/3248	242 sets	
63905	12.00R20	18	RF/GF 118	177/80.3	8.5	22/17.5	154/151 & K	12.4/315	44.3/1125	120/830-120/830	8270/3751-7610/3452	225 sets	
63919	11R22.5	16	RF/GF 118	119/53.9	8.0	21.0/16.5	150/147 & K	11.5/293	42.7/1085	120/830-120/830	6610/2998-6005/2724	275 pcs	
63924	11R24.5	16	RF/GF 118	124/57.6	8.3	24/19	149/146 & M	10.9/279	43.5/1104	120/830-120/830	7160/3248-6610/2998	265 pcs	