



- Wheel position : Drive
- For highway and regional use
- Good water drainage and anti side slip
- Superior traction
- Good resistance to wear

RF/GF 539

| Product Number | Tire Size | PR | Pattern | Weight (lbs/kg) | Rim Size (in) | Tread Depth (32nds/m m) | Load Index S/D & Speed S | Section Width (in/mm) | Overall Diameter (in/mm) | Max. Air Single-Dual (psi/kpa) | Load Capacity Single-Dual (lbs/kg's) | Qty/40'HC | Price |
|----------------|-------------|----|-----------|-----------------|---------------|-------------------------|--------------------------|-----------------------|--------------------------|--------------------------------|--------------------------------------|-----------|-------|
| 63909 | 295/80R22.5 | 16 | RF/GF 539 | 146/66.0 | 9.00 | 28.5/22.5 | 150/147 & L | 11.7/298 | 41.6/1056 | 120/830-120/830 | 7385/3350-6779/3075 | 250 pcs | |
| 63911 | 295/80R22.5 | 18 | RF/GF 539 | 147/67.0 | 9.00 | 28.5/22.5 | 152/149 & L | 11.7/298 | 41.6/1056 | 130/900-130/900 | 7826/3550-7165/3250 | 250 pcs | |